

Ecoglo® RM Series

Standard Photoluminescent Exit Sign

The Ecoglo® RM Standard Series Photoluminescent Exit Signs are the favoured solution to ensuring that your facility is equipped with the safest backup technology in an emergency. With no electricity or battery required, our code compliant photoluminescent exit signs will illuminate your path after being charged by natural or artificial light.

If requested, the Ecoglo® RM Standard Series signs come with a clear anodized aluminum frame and a universal mounting kit that guarantee the most efficient installation procedure for any location. Ecoglo® Photoluminescent RM standard series signs are rugged, require no electricity, reduce maintenance costs and as a result, provide the lowest life cycle costs available for an exit sign.



PRODUCT FEATURES

- LEED points qualified for energy conservation and sustainability
- ULC S572 listed for Photoluminescent and Self-Luminous Exit Signs
- Minimum 120 minute emergency operation
- 50/75-foot visibility rating
- No electricity or batteries required
- Requires exposure to at least 54 lux (5-foot candles) of LED, fluorescent, metal halide, mercury vapour, or other 3.5-4.5K light illumination for a minimum of 60 minutes to become fully operational
- Indoor installation
- Standard twenty-five (25) year warranty
- Non-toxic, non-radioactive
- ULC testing/listing no. E344049/4RG2



BIMready

See back for details.

Ecoglo[®] RM Series

Standard Photoluminescent Exit Sign



Ceiling Mounting Style



Flag Mounting Style



Ceiling Mounting Style

MODEL SELECTION RM - (DIRECTION) (RATING) (FRAME)

ISO Standard requires an arrow with the Running Man symbol at all times. Arrow points to direction of egress.
Signs over doors have arrow pointing down.

Sides and Direction

1-Sided

- RD** Right-facing running man with down arrow
- LA** Left-facing running man with arrow
- RA** Right-facing running man with arrow
- RU** Right-facing running man with up arrow
- BA** Running man with bi-directional arrows*

2-Sided

- SA** Single direction with arrows
- DA** Bi-directional with arrows*

* Special order only, subject to availability.
Standard mounting kits not compatible with bi-directional signs.

Frame and Mounting Kit

- (blank):** No frame
- CA:** Clear anodized aluminum frame and mounting kit

Visibility (Feet) Size: Framed / Unframed

- 50 Feet:** 16.2" x 9.5" [411mm x 241mm] / 15.5" x 8.8" [393mm x 223mm]
- 75 Feet:** 19.6" x 11.6" [498mm x 296mm] / 18.9" x 10.9" [480mm x 278mm]
- 50 Bi-Directional:** 22.9" x 9.5" [582mm x 241mm] / 22.2" x 8.8" [564mm x 223mm]
- 75 Bi-Directional:** 27.4" x 11.6" [695mm x 296mm] / 26.7" x 10.9" [677mm x 278mm]

Example 1: RM-RD50

1-Sided, Right-facing running man with down arrow,
No frame

Example 2: RM-SA75-CA

2-Sided, Single direction with arrows, 75-Foot, Clear
anodized aluminum frame and mounting kit

Contact Kinesik Engineered Products for the
name of a dealer near you.

KINESIK Engineered Products Incorporated

2213 North Sheridan Way
Mississauga, Ontario L5K 1A3
Canada

Phone: 855.364.7763
Fax: 800.769.4463
www.kinesik.ca

Distributor

